



### SPECIFICATION/DESCRIPTION:

Plug-in connected lamp ( infrared sensor + emergency lighting are in one ), match with different country socket standard

**INPUT VOLTAGE:**220-240AC 50/60Hz

**LED POWER:**1W(LED)

**INDUCTIVE TYPE:** infrared induction

**INDUCTIVE DISTANCE:**3-5 meters

**BATTERY:** li-ion battery 3.7V 0.8Ah

**DURATION:**2.5 hours

**INSTALLATION:** special socket

**EMG:** emergency in event of power off

### INDUCTION FEATURES

- Infrared induction, AC lighting starts when the human body is close to 3-5 meters.
- If ambient brightness  $\leq 10\text{LUX}$ , light on for 3-6 minutes then OFF, this can be extended.
- If ambient brightness  $\geq 15\text{LUX}$ , always light on, stop induction
- If power off or pull out the lamp, then emergency lighting is activated.

### STANDARD

EN 60598-1, EN 60598-2-22, EN 61347-2-7, EN 61000-2-3, EN 61000-3-3, EN 55015, EN 61547, IEC TR 62778, Certificate: CE, EMC

Besteil-Nr	Type	Power	Battery	Emergency	Duration	Sensing	Packing LxWxH	Qty Weight	
								Pcs	Kg
50002070	LCDJ-L0041	1W	3.7V0.8Ah Li-ion	1W	2.5H	Infrared	450X360X150	50	8
50002080	LCDJ-L0042	1W	3.7V0.8Ah Li-ion	1W	2.5H	Infrared	450X360X150	50	8