



### SPECIFICATION/DESCRIPTION:

Plug-in connected lamp (sound control + emergency lighting are in one ), suitable for different country socket standard

**INPUT VOLTAGE:**220-240AC 50/60Hz

**LED POWER:**1W(LED)

**INDUCTIVE TYPE:** sound control

**INDUCTIVE DISTANCE:**≥50DB

**BATTERY:** li-ion battery 3.7V 0.8Ah

**DURATION:**2.5 hours

**INSTALLATION:** pluggable

**EMG:** emergency in event of power off

### INDUCTION FEATURES

- Sound induction, AC lighting starts when the sound of induction is ≥50DB.
- If ambient brightness ≤ 10LUX, light on for 3-6 minutes then OFF, this can be extended.
- If ambient brightness ≥15LUX, always light on, stop induction
- If power off or pull out the lamp, then emergency lighting is activated.

### STANDARD

EN 60598-1, EN 60598-2-22, EN61347-2-7, EN61000-2-3, EN61000-3-3, EN55015, EN61547, IEC TR62778, Certificate: CE, EMC

Besteil-Nr	TypeNo	Power	Battery	Emergency	Duration	Sensing	Packing	Qty Weight	
							LxWxH	Pcs	Kg
50002050	LCDJ-L0046	1W	3.7V0.8Ah Li-ion	1W	2.5H	Sound	450X360X150	50	8