


LC-D1020 LED



SPECIFICATION/DESCRIPTION: LED driver and Emergency power combined , configured with 18-48V LED module, suitable for different lights, provide battery charge and discharge, with DALI-2 control function or individual auto-test function.								
APPLICATION RANGE : downlight, panel light, ceiling light etc.								
WORKING VOLTAGE: 220-240VAC 50-60Hz	OUTPUT VOLTAGE: 18-48V							
POWER FACTOR: 0.95	LED WORKING CURRENT: 500mA							
EMERGENCY POWER: 2.5-5W	OUTPUT MODE: constant power output							
AMBIENT TEMPERATURETA: 0...55°C	WARRANTY: 3Years							
AUTO TEST FEATURES Automatic commissioning Performs 20 second functional test every 30days Rated duration test every 52 weeks in accordance with EN 50172:2004 The product will automatically choose one random date from 1-30 days as base date for calculating the rated duration test date. Indication through a bi-colour LED								
STANDARD EN 60598-1, EN 60598-2-22, EN60598-2-1, EN61347-1, EN61347-2-7, EN61347-2-13, EN62031, EN62471, EN61000-3-2, EN61000-3-3, EN55015, EN61547, IEC TR62778, DALI-2 protocol: 101 102 202 104 251 252 253 254 207 Certificate: CE, EMC								
LC-D1020LED Series								
Type No	Input	DC Output	Battery	Power	Function	Qty	Weight	Packing
61203010	220-240V	18-48V	LiFePO4 6.4V/1.5AH	2.5W	Autotest	20pcs	6Kgs	29X23X21CM
61203011	220-240V	18-48V	LiFePO4 6.4V/3.0AH	5.0W	Autotest	20pcs	8Kgs	29X23X21CM
61213010	220-240V	18-48V	LiFePO4 6.4V/1.5AH	2.5W	DALI-2	20pcs	6Kgs	29X23X21CM
61213011	220-240V	18-48V	LiFePO4 6.4V/3.0AH	5.0W	DALI-2	20pcs	8Kgs	29X23X21CM