

### SPECIFICATION/DESCRIPTION:

LED Emergency Sign Light: maintained working mode, configured with driver, provide battery charge and discharge, with DALI-2 function or individual auto-test function

**INPUT VOLTAGE:** 220-240AC 50/60Hz

**EFFICACY:** 130Lm/W(LED)

**LUMINOUS BODY:** 3MM light guide plate

**LUMINANCE:** 46 2cd/

**PATTERN BOARD:** 2.0mm PMMA (can be replaced)

**WARRANTY:** 3Years

### AUTO TEST FEATURES

Performs 20 second functional test every 30days

Rated duration test every 52 weeks in accordance with EN 50172:2004

The product will automatically choose one random date from 1-30 days as base date for calculating the rated duration test date.

Indication through a bi-colour LED


### STANDARD

EN 60598-1, EN 60598-2-22, EN61347-2-7, EN61000-2-3, EN61000-3-3, EN55015, EN61547, IEC TR62778, EN 62034, IEC 62386

DALI No.6255, (LC-DZ001)

DALI-2 protocol: 101 102 202 104 250 251 252 253 254

Certificate: CB, CE, EMC



Besteil-Nr	Type No	Window	Display	Battery	Function	Packing	Qty	Weight
41703011	LCDJ-AD0001-C	2X1W	Double	3.6V2.0Ah Ni-Mh	Autotest	450X380X270	10pcs	20Kg
42703011	LCDJ-AD0001-CD	2X1W	Double	3.6V2.0Ah Ni-Mh	DALI-2	450X380X270	10pcs	20Kg
41603011	LCDJ-AD0001-D	1W	Single	3.6V1.2Ah Ni-Mh	Autotest	380X370X240	10pcs	14Kg
42603011	LCDJ-AD0001-DD	1W	Single	3.6V1.2Ah Ni-Mh	DALI-2	380X370X240	10pcs	14Kg