

**SPECIFICATION/DESCRIPTION:**

LED Emergency Sign Light: maintained working mode, configured with driver , provide battery charge and discharge, with DALI-2 function or individual auto-test function

**INPUT VOLTAGE:**220-240AC 50/60Hz

**EFFICACY:**130Lm/W(LED)

**LUMINOUS BODY:** 4MM light guide plate

**LUMINANCE:**52 2cd/

**PATTERN BOARD:** 2.0mm PMMA (it can be replaced)

**WARRANTY:**3Years

**AUTO TEST FEATURES**

Performs 20 second functional test every 30days

Rated duration test every 52 weeks in accordance with EN 50172:2004

The product will automatically choose one random date from 1-30 days as base date for calculating the rated duration test date

Indication through a bi-colour LED



**STANDARD**

EN 60598-1, EN 60598-2-22, EN61347-2-7, EN61000-2-3, EN61000-3-3, EN55015, EN61547, IEC TR62778, EN 62034, IEC 62386

DALI No.6255,(LC-DZ001)

DALI-2 protocol: 101 102 202 104 250 251 252 253 254

Certificate:CB,CE,EMC



H02



H03



H04



H05



H06



H07

Besteil-Nr	Type No	light	Battery	Display	Function	Packing	Qty	Weight
41301150	LCDJ-SL0015	1W	3.6V1.2Ah Ni-Mh	Single	Autotest	340X2290X280	20Pcs	16Kg
42301150	LCDJ-SL0015-D	1W	3.6V1.2Ah Ni-Mh	Single	DALI-2	340X2290X280	20Pcs	16Kg